

UPK-50-F

<https://www.gigahertz-optik.com/en-us/product/upk-50-f/>

Product tags:



Description

ODM98 integrating sphere for intensity, reflectance and transmittance measurement applications

The UPK-50-F integrating sphere with ODM98 coating is designed for universal use in light intensity, reflectance and transmittance measurement applications. The 50 mm diameter integrating sphere with 10 mm diameter measurement and two auxiliary ports in $\pm 8^\circ$ orientation to the measurement port offers high light throughput required in light sensitive applications within the spectral range from 250 nm to 2500 nm. Its unique collar baffle design greatly avoids direct illumination of the detector port from the light input port in a conventional 90° port position sphere design. The baffle also makes it possible to operate up to 4 detectors or fiber light guide connectors on the sphere at the same time. The detector ports provides an interface for direct mounting of Gigahertz-Optik's PD-11, TD-11 and VL-11 type light detectors and UFC-11 type fiber connectors.



UPK-50-F

Calibration

Gigahertz-Optik's calibration laboratory offers traceable spectral radiant power sensitivity calibration in the wavelength range from 250 nm to 1800 nm. For special cases please contact our sales team.

Specifications



General	
Short description	Integrating sphere for the configuration as reflection measurement device.
Main features	Compact integrating sphere with synthetic ODM98 coating. 10 mm measurement port. Two ports in $\pm 8^\circ$ orientation to the measurement port. Detectorport vor 11-type detectors and fiber connectors.
Measurement range	Sphere Diameter: 50 mm
	Measurement port: One. 10 mm diameter
	Baffle: Yes. Collar type
	Application ports: Two in $\pm 8^\circ$ orientation to the measurement port. With port plugs.
	Detector port: One. 11 mm Diameter. Optional two more
Typical applications	Coating: ODM98
	Integrating sphere for the configuration for reflection measurements.
	depends on configuration
Product	
Coating	ODM98
Sphere diameter	50 mm
Measurement Port Diameter	10 mm
Measurement Port Diameter	10 mm. Supplied with ODM98 coated plugs.
Detector port	1 x UP-DP-11 (PD-11, TD-11, VL-11, UFC-11)
	up to three more UP-DP-11 in $\pm 90^\circ$ position can optional supplied

Mounting	M6 and 1/4" threaded holes
----------	----------------------------

Downloads

Type	Description	File-Type	Download
Drawing	UPK-50-F	pdf	https://www.gigahertz-optik.com/assets/Uploads/100908.pdf

Configurable with

Product Name	Product Image	Description	Go to product
UFC-11		Fiber adapter for use with UP and UM type integrating spheres. Features: SMA, FC, SC and ST connectors.	https://www.gigahertz-optik.com/en-us/product/ufc-11/
PD-11 Series		Detector head with DP-11 mount	https://www.gigahertz-optik.com/en-us/product/pd-11-serie/

Purchasing information

Article-Nr	Modell	Description
Product		
15296144	UPK-50-F	Integrating sphere for reflexion, transmission and radiant power. 50 mm / ~ 2 inch hollow sphere made by ODM98. CNC machined housing. Five application ports, one detector port.

Contact, Calibration, Service & Support

We are known worldwide for excellent technical consulting and after sales support. Contact us to find together the best solution for you. Our services:

- Technical Consulting & Sales
- After-Sales Support
- Calibrations & Re-Calibrations ([ISO/IEC 17025 Calibration Services](#), [factory calibration](#), [Calibration of Third-Party Products](#))
- Repairs & Updates
- OEM & Feasibility Consulting of Customized Solutions

[Send us your inquiry](#) or contact us by phone or e-mail. We would welcome your feedback too or review us on [Google](#).

Gigahertz Optik GmbH (Headquarter)

Tel.: +49 (0)8193-93700-0
Fax: +49 (0)8193-93700-50
info@gigahertz-optik.de

An der Kaelberweide 12
82299 Tuerkenfeld, Germany

Gigahertz-Optik, Inc. (US office)

Phone: +1-978-462-1818
info-us@gigahertz-optik.com

Boston North Technology Park
Bldg B - Ste 205
Amesbury, MA 01913 USA